

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3316B

SIMOTICS SD Add - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area																	
Electrical data																	
U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	250.00	-/-	430.00	1490	1600.0	96.0	96.2	95.9	0.87	0.85	0.78	7.2	2.1	2.8	IE3
690	Y	50	250.00	-/-	250.00	1490	1600.0	96.0	96.2	95.9	0.87	0.85	0.78	7.2	2.1	2.8	IE3
460	Δ	60	250.00	-/-	380.00	1791	1330.0	96.2	96.1	95.4	0.86	0.83	0.76	8.0	2.6	3.0	IE3
460	Δ	60	290.00	-/-	435.00	1788	1550.0	96.2	96.3	95.8	0.87	0.84	0.78	6.9	2.2	2.6	IE3
460	Δ	60		300	340.00	1792	1170.0	96.2	96.0	95.1	0.86	0.83	0.76	8.8	3.0	3.4	MG1
IM B3 / IM1001			FS 315 L				IP55	UKCA		IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 31.4 s 52.1 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 91 dB(A) ^{2) 3)}	81 / 96 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	4.5500 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C4	6319 C4	Thermal class	F
permissible lateral force on (N)	X ₀ : 9300	X _{0.5} : 8650	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Net weight of the motor	1400 kg
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	(Standard) Flat type lubricating nipple acc. DIN 3404		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the angle 45°, socket right	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5
Contact screw thread	6xM12	Cable gland	2 plugs

Notes:		
I_A/I_N = locked rotor current / current nominal	1) L_{10mh} according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_A/M_N = locked rotor torque / torque nominal	2) at rated power / at full load	
M_B/M_N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5533-3AB63-4AA3						
© INNOMOTICS 2023				rev.	creation date	language	Page
				951	2023-12-19	en	1/1